


# Micro-SD Card Socket Connector

## micro SD 1.68

**Applications** | Mobile phone, Computer, Laptop, Medical equipment, Video recorder, Smart Car



- ▶ micro-SD Card Socket
- ▶ Push In – Push Out (Simple Installation)
- ▶ Application structure Card Detect Switch

## Specifications

Current Rating	Contact Resistance	Insulation Resistance	Dielectric Strength	Temperature Range
0.5A/Pin	60mΩ [Max.]	1,000MΩ [Min.]	AC 500V	-40°C ~ 85°C

## Mating Size & Product No.

PINS	PITCH	WIDTH	HEIGHT	LENGTH	CODE
8	1.10	15.95	1.68	13.85	MS110-C10B-C16-H

# Micro-SD Card Socket Connector

## micro SD 1.68

**Applications** | Mobile phone, Computer, Laptop, Medical equipment, Video recorder, Smart Car

## Product Specification

Ratings	Rated current	0.5A/Pin	Operating temperature range	-40°C to +85°C 1	Storage temperature range	-5°C to +40 °C (With packing)
	Rated voltage	AC 125V	Operating humidity range	10% to 80% RH 2	Storage humidity range	65%RH

1) Including terminal temperature rise.

2) Storage area is to be free of corrosive gases and dew formation.

Items	Specifications	Conditions
1. Contact resistance	60mΩ [Max.]	- Open circuit voltage: 20mV. - Test current: 10mA.
2. Insulation resistance	1,000MΩ [Min.]	- Test voltage: 500V d.c. - Test time: 1 minute ± 5 seconds.
3. Withstanding voltage	No flashover or dielectric breakdown	AC 500V for 1minute
4. Card Insertion force & Withdrawal force	Initial : 500 ±200 gf After : 500 ±200 gf	- Push-pull gauge at 25±3m/min speed.
5. Vibration	- MAX. Change from Initial contact resistance 40mΩ MAX.	- Vibration frequency range : 10-55-10Hz - Total amplitude : 1.52mm - Sweep time : 30sec - Duration : 2h each (6h in total)
6. Durability	- MAX. Change from Initial contact resistance 40mΩ MAX. - Card Insertion Force & withdrawal force 500 ±200 gf	- Attach and detach 10,000 times. - Attach and detach 600 time / Hr or less
7. Temperature and Humidity cycle	- MAX. Change from Initial contact resistance 40mΩ MAX. - Insulation resistance : 100MΩ Min	- 40±3(°C) : 30 minutes → 85±2(°C) : 30 minutes, 96 cycles
8. Humidity	- MAX. Change from Initial contact resistance 40mΩ MAX. - Insulation resistance : 100MΩ Min	- Temperature : 40°C±2°C - Relative humidity : 90% RH to 95% RH - Duration : 96hr
9. Salt mist	- MAX. Change from Initial contact resistance 40mΩ MAX. - Insulation resistance : 100MΩ Min	- Salt water concentration : 5±1% Weight ratio - Temperature : 35°C±2°C - Duration : 72h
10. Heat	- MAX. Change from Initial contact resistance 40mΩ MAX. - Insulation resistance : 100MΩ Min	- Temperature : 105±2°Ctio - Duration : 96h

## Materials / Finish

Part	Materials	Finish	UL Regulation
Base	LCP	Black	UL94V-0
Terminal	Copper Alloy	Au, Ni plated	-
Cover	Nickel silver	Au, Ni plated	-
Switch A	Copper Alloy	Au, Ni plated	-
Switch B	Copper Alloy	Au, Ni plated	-
Ejector	Stainless Steel	-	-
CAM Stick	Stainless Steel	-	-
Spring	Stainless Steel	-	-

# Micro-SD Card Socket Connector


## micro SD 1.68

**Applications** | Mobile phone, Computer, Laptop, Medical equipment, Video recorder, Smart Car

## FEATURES AND ADVANTAGES


### ► CARD INSERT

- Easy card installation (Push In – Push Out)
- Improving product quality reliability



### ► CARD DETECTION

- Normal [OPEN] --> Card inserted [CLOSE]
- Strengthen contact stability
- Improving product quality reliability



# Micro-SD Card Socket Connector

## micro SD 1.68

**Applications** | Mobile phone, Computer, Laptop, Medical equipment, Video recorder, Smart Car

### Product Drawing

